

32CrMoV12-28

W.Nr. 1.2365

Properties

hot working tool steel; high level toughness
enduse = extrusion dies, casting moulds

Chemical composition

C=0,28-0,35	Si=0,10-0,40	Mn=0,15-0,45	P=max.0,025	S=max.0,010
Cr=2,70-3,20	Mo=2,50-3,00	V=0,40-0,70		

DIN EN ISO 4957

Grade equivalents Similar grades

BH 10 BS	----- GB	32CDV12 28 AFNOR	SKD7 JIS	19541 CSN
H 10 AISI / SAE	30CrMoV1227KU UNI	----- SS	3Ch3M3F GOST	F.5313 UNE

General conditions

Heat treatment =+A DIN EN ISO 4957

Hardness max. 229 HB

Surface surface flaws / cracks if any are removed by polishing.
cleaning marks/scale pitting/peripheral decarburisation within
the standard machining allowance is allowed.

US test SEP 1921 group 3, class D/d or
EN 10228-3 quality grade 3, 100% scanning or
specific FBH eq.

Degree of Purity DIN 50 602, K4 max. 20

Microstructure soft annealed / acc. to SEP 1614, max. figures as follows :
segregation = SA1-SA4; SB1-SB4;SC1-SC4;SD1-SD4
microstructure = GA1-GA5; GB1-GB4;GC1-GC2;GD1-GD2;GE1

Hot rolled and/or forged, peeled and/or turned

Ø 15 - 403 mm

Tolerances - 0 / + 0,8 - 4,0 mm (dep. on dia) or specific tol.
Lengths 2,5 - 5,5 m or specific lengths ends of bars are sawn

Hot rolled, black and/or Hot rolled all sides machined

20 - 105 x
90 - 610 mm

Tolerances EN 10058 positiv allowance only or
DIN 50602 positiv allowance only or
specific tol.
Lengths 2,5 - 5,5 m or specific lengths ends of bars are sawn

Hot rolled and/or forged, black Hot rolled and/or forged, black all sides machined

20 x 20 -
300 x 300 mm

Tolerances EN 10059 positiv allowance only or
DIN 7527 / 6 positiv allowance only or
specific tol.
Lengths 2,5 - 5,5 m or specific lengths ends of bars are sawn

Forged, black and/or forged all side machined

100 - 455 x
120 - 1.050 mm

Tolerances DIN 7527 / 6 positiv allowance only or
specific tol. positiv allowance only
Lengths 2,5 - 5,5 m or specific lengths ends of bars are sawn

Test certificate

EN 10204/3.1 with chem. Analysis; hardness HB ; heat treatment ; US test
(copy of original on our letter head !)

- supply range file - issued: 20.02.2009 rev. 1